

COLLABORATE WITH **SPEED** AND *PRECISION*

imagePROGRAF iPF670 MFP



imagePROGRAF iPF670 MFP
Large Format Multi-Functional Printer
for printing, scanning and copying
of your CAD applications.

Copy and Print technical drawings
up to 24" (A1) size with an easy-to-
use touchscreen interface.

Scan to multiple locations,
including your network, email and
to the cloud to allow you to share
documents the way you want.



imagePROGRAF

Canon

no one sees print like you



Advanced Preview

Edit scanned document before printing to reduce wastage and costs



23" touchscreen input

Large touchscreen for ergonomic and natural input



Direct Print & Share

Canon propriety utility to allow sharing and printing of documents with minimal training and user experience



Sub-ink tank system

Ink can be changed without interrupting a print job



Accounting Manager

Software helps keep track of printing costs

At a glance

- 24" (A1) printing width
- 25" scanning width
- 2400 x 1200 dpi
- Min line width 0.02mm
- 4pl ink droplet
- Borderless printing
- Accurate scalable copies



imagePROGRAF iPF670MFP

Printer Specifications



| General printer specifications | |
|---|---|
| Model | iPF670 |
| Class | 24-inch |
| Ink Type | Dye and pigment reactive ink: BK, MBK, C, M, Y |
| Maximum Print Resolution | 2,400 x 1,200dpi |
| Installation | User installation |
| Printer Stand | Assembly type |
| Dimensions, Weight (Net) W x D x H (mm), (Kg) | |
| Main unit + Printer Stand ST-27 (with a basket open) | W997 x D887 x H1062mm (ST-27: When with basket open) W997 x D1100 x H1062mm (ST-27: When a basket is at the extended position for flatbed stacking) Weight: 53.7kg (ST-27, roll holder included, no inks, no print heads) |
| Main unit (with a basket open) | W997 x D698 x H507mm Weight: 43.0kg |
| Dimensions, Weight (Packaged) W x D x H (mm), (Kg) | |
| Main unit (with a palette included) | W1127 x D830 x H773mm, Weight: 72.0kg |
| Printer Stand (ST-27) | W1083 x D766 x H350mm, Weight: 19.0kg |
| Power Supply | |
| Input power | AC 100 - 240V (50-60 Hz) |
| Power consumption | Operation: 140W or less |
| At the low power mode 220 V - 240 V | 5W or less |
| Default setting for the time to enter the Sleep mode | approx. 5min |
| Power off (standby) | 0.5W or less |
| Operational Environment | |
| Temperature: 15 - 30°C, Humidity: 10 - 80 % (Condensation free) | |
| Acoustic Noise | |
| Acoustic pressure | Operation: approx. 47dB (A) (Plain paper, Standard printing mode, Line Drawing/Text). Standby: 35 dB (A) or less. Measured in the above conditions, based on ISO 7779 |
| Acoustic power (LWAd) | Operation: approx. 6.4 Bels (Plain paper, Standard printing mode, Line Drawing/Text). Measured in the above conditions, based on ISO 7779 |
| Minimal Line Width | |
| 0.02mm (Theoretical value) | |
| Line Accuracy | |
| ±0.1% or less. User adjustments necessary. Printing environment and media must match those used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only. | |
| Detector and Adjustment | |
| Registration adjustment | Automatic / Manual |
| Banding adjustment (Line Feed adjustment) | Automatic / Manual |
| Line length adjustment | Manual |
| Head slant adjustment | Automatic / Manual |
| Colour calibration | No |
| Head gap adjustment | Automatic / Manual (6 levels) |
| Non-firing detection | Yes |
| Non-firing compensation | Yes |
| Roll media remaining detection function | Yes |
| Memory | |
| Standard memory | 256 Mbyte |
| Expansion slot | No |
| Firmware | |
| Languages - Printer Language | GARO (Graphic Arts language with Raster Operations), HP-GL/2, HP RTL |
| Languages - Job Control | CPCA |
| Languages - Status Reply | CPCA, SNMP-MIB, Standard MIB, Canon-MIB |
| Type | Flash ROM |
| Update | Updated from USB, Ethernet port (Utility use) |
| Operation Panel | |
| Display | Large LCD: 160 x 128 dots; Key x 13, LED x 5 |
| Language on operation panel | US-English, Japanese |
| Languages | US-English, French, German, Italian, Spanish, Chinese (simplified), Korean, Russian, Brazilian portuguese language, Japanese (Kanji) |
| Hard Disk Drive | |
| No | |
| Interface | |
| USB - Type | Built-in |
| USB - Type | Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer Series B (4 pins) |
| USB - Connector Type | Built-in |
| Ethernet - Type | Built-in |
| Ethernet - Standard | IEEE 802.3 10base-T, IEEE 802.3u 100base-TX / Auto-Negotiation, IEEE 802.3ab 1000base-T / Auto-Negotiation, IEEE 802.3x Full Duplex, IEEE 802.3az EEE |
| Ethernet - Protocol | SNMP (Canon-MIB supported), HTTP, TCP/IP (IPv4/IPv6) |
| Expansion Slot | |
| No | |
| Print Head | |
| Model | PF-04 |
| Type | Bubble-jet on demand |
| Head configuration | 6 colours integrated type (6 chips per print head x 1 print head) |
| Nozzle pitch | 600dpi x 2 lines = 1200dpi |
| Nozzle per chip | MBK: 5, 120 nozzles, each other colour: 2, 560 nozzles |
| Droplet size | Minimum 4pl (per colour) |

| Ink Tank | | | |
|--|--|---------------------------------------|-------------------|
| Model | MBK/BK/C/M/Y - PFI-107 (130ml per ink tank) | | |
| Supply | Tubing system (supplies ink from independent ink tanks set in the printer through tubes) | | |
| Colours | BK/MBK/C/M/Y | | |
| Capacity | Bundled starter ink : 90ml, sales ink : 130ml | | |
| Level detection | Detected by dot count and electrode (Empty) | | |
| Smart chip | Each ink tank is equipped with EEPROM which stores its ink level | | |
| Cutter | | | |
| Model | - | | |
| Type | Standard: Automatic horizontal cutting (Rotary cutter) | | |
| Replacement | Service replacement | | |
| Media Feed and Output | | | |
| Roll paper | One Roll, top loading, front output | | |
| Cut sheet | Top-feeding, front output (Manual feed using media locking lever) | | |
| Paper path switch (roll/cut sheet) | Manually switchable by user | | |
| Delivery direction | Face-up, front side | | |
| Maximum stacking number of delivered print | 1 sheet: In case of the regular basket position. Approx. 20 sheets: In case the basket is at the extended positions. (Except for the cases where delivered prints are rolled in because of environmental impact and media curls.) | | |
| Types of media stackable on the extended basket | One Roll, top loading, front output | | |
| Usage environment of the extended basket / Image | At normal temperature and normal humidity (15°C 30% - 30°C 60%) / Image: Line drawing (images equivalent to the Cottage.) | | |
| Sizes of media stackable on the extended basket | Extended position A: A1 portrait or Width 24" x Length 36" Extended position B (Flatbed stacking): A2 landscape or Width 24" x Length 18" | | |
| Media Size - Roll paper (width) | | | |
| ISO | A3, A2, A2+, A1 | | |
| JIS | B4, B2 | | |
| ARCH | 24" | | |
| Others | 10", 14", 16", 17", Banner (300mm) | | |
| Media Size - Cut Sheet | | | |
| ISO | A4, A3, A3+, A2, A2+, A1, A0 B4, B3, B2" | | |
| DIN | C4, C3, C2, | | |
| JIS | B4, B3, B2 | | |
| ANSI | 8.5 x 11", 8.5 x 14", 11 x 17", 13 x 19", 17 x 22", 22 x 34" | | |
| ARCH | 9 x 12", 12 x 18", 18 x 24", 24 x 36" | | |
| Photo | 20 x 24", 18 x 22", 14 x 17", 12 x 16", 10 x 12", 10 x 15", 16 x 20" (US Photo size) | | |
| Poster | 20 x 30", 300 x 900mm | | |
| Others | 13 x 22" | | |
| Media Thickness | | | |
| Roll paper | 0.07 - 0.8mm | | |
| Cut sheet | 0.07 - 0.8mm | | |
| Maximum Outside Diameter of Roll Paper | 150mm or less | | |
| Media Core Size | Internal diameter of roll core: 2" / 3" | | |
| Media Width | | | |
| Roll paper | 254 (10") - 609.6 (24")mm | | |
| Cut sheet | 203.2 (8") - 609.6 (24")mm | | |
| Minimum Regular Format Size (Vertical) | | | |
| Roll paper | 203.2mm (8") | | |
| Cut sheet | 279.4mm (11"): Letter size (long side) | | |
| Maximum Printable Paper Length | | | |
| Roll paper | 18m (Varies according to the OS and application) | | |
| Cut sheet | 1.6m (Varies according to the OS and application) | | |
| Margins - Recommended area | | | |
| Roll paper | Top: 20mm, Bottom: 5mm, Left and Right: 5mm | | |
| Cut sheet | Top: 20mm, Bottom: 23mm, Left and Right: 5mm | | |
| Margins - Printable area | | | |
| Roll paper | Top: 3mm, Bottom: 3mm, Left and Right: 3mm | | |
| Roll paper (borderless printing) | Top: 0mm, Bottom: 0mm, Left and Right: 0mm | | |
| Cut sheet | Top: 3mm, Bottom: 23mm, Left and Right: 3mm | | |
| Borderless Printing | | | |
| Media width | 10" (254mm), B4 (257mm), A3 (297mm), Banner (300mm), 14" (356mm), A2 (420mm), A2+/17" (432mm), B2 (515mm), A1 (594mm), 24" (610mm) | | |
| Regulations | Electrical safety regulations | Electromagnetic interface regulations | Other regulations |
| Australia | RCM | RCM | |
| New Zealand | | RCM | |
| Environment certifications | | | |
| ENERGY STAR, RoHS directive | | | |
| Option | | | |
| Roll Holder Set (for both 2-inch and 3-inch core roll media) | | RH2-26 | |
| Stand Basket | | ST-27 | |
| Consumables | | | |
| Ink Tank | | PFI-107 MBK / BK / C / M / Y | |
| Print Head | | PF-04 | |
| Maintenance Cartridge | | MC-10 | |

Scanner Specification Comparison

| M 25 | |
|--|---|
| Scan width (inches) | 25" (63.5cm) |
| Document width (inches) | 27" (68.6cm) |
| Body width (inches) | 34.2" (86.8cm) |
| Body depth (inches) | 14.4" (36.6cm) |
| Body height (inches) | 7.3" (18.5cm) |
| Weight | 18Kg |
| CIS Configuration | SingleSensor |
| Illumination | Full width dual LED illumination |
| Image quality | Better |
| Stitch performance | Set in manufacturing (3) |
| Front/rear exit | Front |
| Document handling - Face up/down | UP |
| Max Document thickness | 2.0mm(1) |
| Paper path | Flat |
| Optical Resolution (dpi) | 1200 |
| Scan speed (cm/sec) 8-bit grayscale & mono @200dpi (2) | 33 |
| Scan speed (cm/sec) 24-bit color @200dpi (2) | 7.6 |
| Interface USB | 3.0 (backward compatible to USB2) |
| Control panel | Start/Stop, Advance/rewind, ASF (Auto Size Finder) read out |

M series notes:

1. Thick documents up to 2mm must be flexible and the paper return guide removed. Some media should be scanned at reduced speeds to obtain optimal image quality. Colortrac cannot guarantee to scan all media. For large media Colortrac recommend the scanner be placed on a flat surface and the operator supports the document as it enters and exits the scanner.
2. The scan rate is proportional across the full range of resolutions supported by the scanner. Actual scan times and quoted top speeds will depend on the host performance and are not guaranteed for all media types. True 200 x 200dpi image capture. Competitors quote scan speeds using 'Turbo', 'Normal' or 'High Speed' modes that reduce image quality whilst suggesting that scan resolution is doubled. These modes use software interpolation to create 'virtual image pixels' from a lower resolution scan thereby increasing the number of pixels in the scan direction (&/or X-direction) in an attempt to simulate higher image resolution. Colortrac SmartLF scanners are designed to scan images fast at the optimum resolution required to capture the original image detail without compromising quality.
3. The SingleSensor is colour calibrated and accurately aligned to within +/- 0.5 pixel during manufacture. If the scanner is used in a stable, general office environment, scanner calibration and / or alignment may only occasionally be required. Operation in mobile, dusty or variable temperature environments may require more frequent scanner maintenance.]

Detailed specifications for M series scanners

| | |
|---|--|
| Scan modes | 16.7 million colour RGB (24-bit) 256 colour RGB adaptive indexed colour palette (8-bit) 256 level greyscale (8-bit) Black & White (1-bit) |
| Digital image processing | 2D Intelligent Adaptive Thresholding (IAT) (1-bit mode) Fixed Threshold Black & White (1-bit mode) (SmartWorks MFP provides additional 'post scan' image processing filters and tools) |
| Colour space | sRGB (with SmartWorks MFP) |
| Colour image processing | Gamma, brightness, black & white point adjustment |
| Media transport system | Straight media path with front entry, rear exit or rewind to front Single driven document hold-up roller Intuitive image up scanning with centre or side document alignment Magnetic media guide to assist in high volume document scanning workflows Automatic Size Finder (ASF) with media width displayed on control panel |
| SingleSensor digital imaging technology | SingleSensor is a full width straight-line contact image sensor of 50,400 pixels; a Colortrac invention - patent pending. Bi-directional long-life LED light system for optimum object illumination and instant-on scanning capability 48-bit primary point colour image capture 16-bit primary point greyscale image capture Panchromatic Black & White |
| Scanner operation & status | Centre-lid mounted control panel with LCD media width display for auto size finder with start, stop, forward and rewind buttons Scanner status indicator LED (green, amber, red) |
| Scan Accuracy | +/-0.1% +/-1 pixel (The achieved scan accuracy may vary depending on the operating environment and the type & thickness of media). |
| Scanner optics & calibration | Chemically treated, scratch resistant, anti-Newton ring (AG) scan glass Automatic SingleSensor calibration. The SingleSensor is colour calibrated and accurately aligned to within +/- 0.5 pixel during manufacture. If the scanner is used in a stable, general office environment, scanner calibration and / or alignment may only occasionally be required. Operation in mobile, dusty or variable temperature environments may require more frequent scanner maintenance. |
| Interface | SuperSpeed USB3 with 3 metre USB3 cable (PC connector compatible with USB2 and USB3 sockets) Local power cable |
| Power requirements & consumption | External power supply 100*240VAC autosensing +/-10%, 50*60Hz Scanner power consumption 53W (scanning), 5W (standby) @ 110V/240V |
| Environmental/Approvals | RoHS compliant and CE, FCC, VCCI, UL, CB, CCC certification. |
| Operating conditions | 10°C - 35°C, 35% - 80% RH non-condensing |
| Stands | Stand must be mounted integral to the printer. Scanner tilted towards user. PC and flat screen VESA mounting kit. Screen can be mounted left or right and on a pole or swing arm. Paper Return Guide - curved to redirect flexible scanned documents forward to operator. Can be lifted off when not required or for scanning thick or non-flexible media. |



For information and services

Canon Australia Pty Ltd 1300 363 440 canon.com.au
 Canon New Zealand Ltd 0800 222 666 canon.co.nz

Canon

