

No one does it
like you

Canon

TRANSFORM YOUR IMAGES INTO WORKS OF ART.

Shooting an image is only half the story. If you want to turn that image into a photograph, you need to be able to print it. The imagePROGRAF PRO-2100 gives your images the quality they deserve while removing the complexity traditionally associated with printing.




Canon imagePROGRAF PRO-2100



MULTI-FUNCTIONAL ROLL UNIT

Load two rolls of media at the same time or use the second roll unit as a take-up reel with intelligent media loading and remaining media estimation



CRYSTAL FIDELITY

The most faithful shoot-to-print workflow with Canon EOS cameras and software



CHROMA OPTIMISER

Balances the reflective properties of dark areas to improve overall print quality



ACCOUNTING MANAGER

Software helps keep track of printing costs



COLOUR CALIBRATION

Built-in sensors read colour density to ensure your last print is as stunning as your first

Key features

- Intelligent Media Handling
- 4.3" Touch Screen
- Borderless Printing
- High-speed L-COA PRO Processor
- Advanced Software and Workflow Solutions
- Compact Design
- Direct USB Drive Printing
- Sub-ink Tank System

This 24 inch wide solution is optimised for proofing, photography and fine art printing.

If you've found it hard to match the quality of your image with your finished print, then the Canon imagePROGRAF PRO-2100 may be for you. We've built on years of credentials in both photography and print to deliver professional quality prints up to 24 inch wide.

imagePROGRAF PRO-2100 SPECIFICATIONS

imagePROGRAF
PRO-2100

Item	Specification
Model	PRO-2100
Class	24"
Ink Type	Pigment Ink
Maximum Print Resolution	2400 x 1200 dpi
Stand Type	Assembly Type

Unpackaged Dimensions W x D x H (mm), Weight (kg)

Main Unit + Stand + Basket	1110 x 984 x 1168 (Basket Opened) 1110 x 766 x 1168 (Basket Closed) Weight: Approx 102 kg (Excluding Roll Holder Set, Ink and Print Head)
Main Unit + Roll Unit + Stand + Basket	Weight: Approx 119 kg (Including Roll Holder Set, Excluding Ink and Print Head)

Packaged Dimensions W x D x H (mm), Weight (kg)

Printer (Main unit with pallet)	1324 x 902 x 1042 mm, Weight: Approx 124 kg
Stand/Basket	1111 x 797 x 223 mm, Weight: Approx 23 kg
Roll Unit	1244 x 562 x 461 mm, Weight: Approx 26 kg

Power Supply

Input Power	AC 100-240 V (50-60 Hz)
Power Consumption	Printing: 93 W or Less
Standby Power Consumption	2.0 W or Less
Power Off (Standby)	0.3 W or Less

Operational Environment

Temperature: 15°-30 °C, Humidity: 10°-80 % RH (no dew condensation)

Acoustic Noise

Acoustic Pressure	Operation Approx. 46 dB (A) Standby: 35 dB (A) or Less
Acoustic Power	Operation Approx. 6.4 Bels or Less

Detector and Adjustment

Registration Adjustment	Automatic/Manual
Banding Adjustment	Automatic/Manual
Line Length Adjustment	Manual
Head Slant Adjustment	Automatic
Colour Calibration	Yes (with a Colour Calibration Notification Function)
Head Gap Adjustment	Automatic/Manual (6 Levels)
Non-firing Nozzle Detection	Yes
Non-firing Nozzle Compensation	Yes
Roll Media Remaining Detection Function	Barcode Print or Estimation Function

Line Accuracy

±0.1 % or Less
User adjustments necessary. Printing environment and media must match those used for the adjustments.
CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only.

Memory

Standard Memory	3 GB
-----------------	------

Firmware

Languages – Printer Language	SGRaster (Swift Graphic Raster)
Type	Flash ROM
Update	Updated from USB, Ethernet Port (Utility use)

Operation Panel

Display	4.3 inch Colour LCD Touch Screen
---------	----------------------------------

Hard Disk

500 GB

Interface

USB B Port – Type	Built-in (Hi-speed USB)
USB B Port – Mode	Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk Transfer
USB B Port – Connector Type	Series B (4 pins)
USB A Port	USB Memory (Direct Print)
Gigabit Ethernet – Type	Built-in
Gigabit Ethernet – Standard	IEEE 802.3 10base-T IEEE 802.3u 100base-TX/Auto-negotiation IEEE 802.3ab 1000base-T/Auto-negotiation IEEE 802.3x Full Duplex
Gigabit Ethernet – Protocol	SNMP (Canon-MIB), HTTP TCP/IP (IPv4/IPv6)
Wireless LAN – Standard	IEEE802.11n/IEEE802.11g/IEEE802.11b
Wireless LAN – Security	WEP (64/128bit) WPA-PSK (TKIP/AES) WPA2-PSK (TKIP/AES)

Print Head

Model	PF-10
Type	Bubble-jet On-demand
Head Configuration	12 Colour Integrated Type x 1 Print Head
Nozzle Pitch	600 dpi x 2
Nozzle Per Chip	18,432 Nozzles (1,536 Nozzles x 12 Colour)
Droplet Size	Minimum 4 pl per Colour

Ink Tank

Model	PFI-1100 (160 ml)/PFI-1300 (330 ml)/PFI-1700 (700 ml)
Supply	Tubing System (with Sub-tank)
Sub-ink Tank Capacity	Each Colour 30 ml
Colours	Pigment 12 Colour (PBK/MBK/C/M/Y/PC/PM/GY/PGY/R/B/CO)
Ink Tank Size – Sales	160 ml, 330 ml or 700 ml
Ink Tank Size – Starter	160 ml
Level Detection	Detected by dot count and electrode
Smart Chip	Each ink tank is equipped with EEPROM which stores its ink level

Cutter

Model	CT-07
Type	Automatic Horizontal Cutting (Rotary Cutter): Standard

Other Consumables

Maintenance Cartridge	MC-30
-----------------------	-------

Media Feed and Output

Roll Paper	One Roll, Front-loading, Front Output
Added Roll Paper	One Roll, Front-loading, Front Output
Cut Sheet	Front-loading, Front Output (Manual feed using media locking lever)
Paper Path Switch (Roll/Cut Sheet)	Manually Switchable by User
Delivery Direction	Face-up, Front side
Media Take-up Unit	Dual Direction – Rolling Take-up

Media Thickness

Roll Paper	0.07°0.8 mm
Cut Sheet	0.07°0.8 mm

Maximum Outside Diameter of Roll Paper

170 mm or Less

Media Core Size

Internal Diameter of Roll Core: 2"/3"

Media Width

Roll Paper	152.4°610 mm
Cut Sheet	152.4°610 mm

Minimum Printable Paper Length

203.2 mm

Margins – Recommended Area

Roll Paper	Top: 20 mm, Bottom: 3 mm, Side: 3 mm
Cut Sheet	Top: 20 mm, Bottom: 20 mm, Side: 3 mm

Margins – Printable Area

Roll Paper	Top: 3 mm, Bottom: 3 mm, Side: 3 mm
Roll Paper (Borderless Print)	Top: 0 mm, Bottom: 0 mm, Side: 0 mm
Cut sheet	Top: 3 mm, Bottom: 20 mm, Side: 3 mm

Borderless Printing

Media Width
Recommended – 515 mm (JIS B2), 594 mm (ISO A1), 10", 14", 17", 24"
Printable – 257 mm (JIS B4), 297 mm (ISO A3), 329 mm (ISO A3-), 420 mm (ISO A2), 6", 8", 12", 16", 20", 22", 300 mm, 500mm, 600mm and Custom Roll Width (154.2-610 mm)
"Printable" size is printed as micro margin technology, that means is not used with hole of platen.

Regulations	Electrical Safety Regulations	Electromagnetic Interface Regulations
Australia	RCM	RCM

Environment Certifications

TUV, CB, EPEAT

Options

Roll Unit	RU-23
2/3" Roll Holder	RH2-29

For information and services contact

Canon Australia Pty Ltd	1800 444 199	canon.com.au/business
Canon New Zealand Ltd	0800 222 666	canon.co.nz/business

Crystal-fidelity



No one does it
like you

Canon